



Color Variants
AL200180

Optional accessories
AA200100
AA200880
AA200882

Installation Accessories
AA200910
VA200080

Product Features
Product name / series name
Color chimney
Typology
Approval certificates CE, Eurasian, G-Mark, VDE
Power cord length (cm) 130
Required cutout size (HxWxD) (mm) 703mm x 781.0mm x 123mm
Height of the chimney (mm)
Height of product, without chimney (mm)
Net weight (kg) 37.106
Oven Control Electronic
Number of speed settings 3-stage + 2 intensive
Max. extraction rate 501
Boost position output recirculating (m3/h) 562.0
Maximum output recirculating air 447
Boost position air extraction (m³/h) 775
Number of lights
Silence level (dBA) 62
Diameter of air duct (mm) 150
Grease filter material
Odor filter No
Operating Mode Convertible: Ducted / Recirculating
Delay Shut off modes 10
Required accessories
Optional accessories AA200100, AA200880, AA200882
Type of lamps used
Total power of the lamps (W)
Grease filter type
Clean filter reminders
Watts (W) 300
Current (A) 10
Volts (V) 220-240
Frequency (Hz) 50; 60
Plug type Gardy plug w/ earthing
Installation Type Built-in
UPC code
Material Glass
Approval certificates CE, Eurasian, G-Mark, VDE
Power Cord Length
Plug type Gardy plug w/ earthing
Overall appliance dimensions (HxWxD) (in) / x x
Product packaging dimensions (HxWxD) (in) 24.01 x 44.88 x 34.25
Height of the chimney (in)
Vertical rise height
Required distance above cooktop/ ranges
Net weight (lbs) 82.000
Gross weight (lbs) 103.000
Motor location Integrated motor in hood body
Maximum CFM
Diameter of air duct (in) top
Diameter of air duct (in) back
Discharge direction
No-return airflow flap No
Power cord length (cm) 130



Color Variants

AL200190

Optional accessories

AA200100

AA200890

AA200892

Installation Accessories

AA200910

VA200090

Product Features

Product name / series name

Color chimney

Typology

Approval certificates

CE, Eurasian, G-Mark, VDE

Power cord length (cm)

130

Required cutout size (HxWxD) (mm)

703mm x 854.0mm x 123mm

Height of the chimney (mm)

Height of product, without chimney (mm)

Net weight (kg)

42.950

Oven Control

Electronic

Number of speed settings

3-stage + 2 intensive

Max. extraction rate

501

Boost position output recirculating (m3/h)

562.0

Maximum output recirculating air

447

Boost position air extraction (m³/h)

775

Number of lights

Silence level (dBA)

62

Diameter of air duct (mm)

150

Grease filter material

Odor filter

No

Operating Mode

Convertible: Ducted / Recirculating

Delay Shut off modes

10

Required accessories

Optional accessories

AA200100, AA200890, AA200892

Type of lamps used

Total power of the lamps (W)

Grease filter type

Clean filter reminders

Watts (W)

300

Current (A)

10

Volts (V)

220-240

Frequency (Hz)

50; 60

Plug type

Gardy plug w/ earthing

Installation Type

Built-in

UPC code

Material

Glass

Approval certificates

CE, Eurasian, G-Mark, VDE

Power Cord Length

Plug type

Gardy plug w/ earthing

Overall appliance dimensions (HxWxD) (in)

/ x x

Product packaging dimensions (HxWxD) (in)

24.01 x 44.88 x 34.25

Height of the chimney (in)

Vertical rise height

Required distance above cooktop/ ranges

Net weight (lbs)

95.000

Gross weight (lbs)

106.000

Motor location

Integrated motor in hood body

Maximum CFM

Diameter of air duct (in) top

Diameter of air duct (in) back

Discharge direction

No-return airflow flap

No

Power cord length (cm)

130

GAGGENAU