



Color Variants

RVF497190
Fully integrated, with ice maker.
Niche width 91.4 cm, Niche height 213.4 cm.

Included accessories

1 x ice cube scoop.
1 x Ice storage container.
large.

Optional accessories

RA450012

Installation Accessories

RA425110
Handle bar, stainless steel, long
RA460020
Connecting element for vertically split appliance fronts (for a flush front).
RVA421924
RVA423141
RVA428924
RVA460000
RVA460020
RVA460900
RVA460910
RVA466900

RVF497190

Vario freezer Expressive series

Fully integrated, with ice maker.

Niche width 91.4 cm, Niche height 213.4 cm.



Highlights

Dark brushed stainless steel interior, refined with solid anthracite aluminium elements.

Warm white and glare-free LED light concept for optimal food presentation in all compartments.

Opening assist for door with two options:

1. Push-to-open function for integration into handleless furniture front 2. Pull-to-open function to facilitate opening the door using a handle

The drawers in the RVC and RVF models are positioned at the same height. With side-by-side installation, the glass shelves and door racks can be aligned on the same level.

Flexible positioning of shelves and door racks through hidden rail system.

Flat dark brushed stainless steel inner door.

Handling

Opening assist for door.

Cushioned door closing system.

User guidance through light and display response to drawer interaction.

Automatic brightness adjustment based on ambient illumination.

Hidden touch display.

Technical features

Dynamic cold air distribution.

Automatic defrosting with defrost water evaporation.

Rest mode certified by Star-K.

When rest mode is active, the appliance can only be opened using a handle.

Open-door and malfunction alarm.

Selected digital services (Gaggenau Home Connect)

Remote control and monitoring.

Remote diagnostics.

Freezing

No-frost technology with fast freezing at -30 °C.

4-star freezer compartment.

Temperature adjustable from -24 °C to -16 °C.

Freezer burn protection.

Oxidation protection.

Warm-white, glare-free LED lighting (3000 K).

2 aluminium-framed safety glass shelves, individually adjustable in height.

Flexible positioning of door racks through hidden rail system.

3 height-adjustable door racks.

3 fully extendable drawers, with cushioned closing system.

Ice maker

Hidden in one drawer for optimised usable space.

With fixed water connection (inlet).

Can be switched off.

Integrated, easy accessible ice cube scoop.

Particle filter for water inlet, integrated in ventilation grille area.

Saturation indicator shown in touch display.

Consumption data

Energy efficiency class D at a range of energy efficiency classes from A to G.

Planning notes

Flat hinge.

Door hinge left, reversible.

Characteristics

Energy Efficiency Class (Regulation (EU) 2017/1369)

D

Average annual energy consumption in kilowatt hour per year (kWh/a)

Sum of volume of frozen compartments

Airborne acoustical noise emissions

Airborne acoustical noise emission class

Product category

Upright freezer

Built-in / Free-standing

Built-in

Color / Material body

Frost free system

Fridge and freezer

Climate class

SN-T

Door panel options

Width of the appliance

894

Depth of the product

608

Dimensions of the packed product (HxWxD)

2260 x 1000 x 745

Required niche size for installation (HxWxD)

2134 x 914 x 610

Warning signal / malfunction

No signal

Defrost

Cover door installation system

Fixed-mounted

Number of drawers/baskets (Stck)

3

Number of freezing flaps (Stck)

0

Lockable door

No

Thermometer freeze section

Not applicable

Light

Yes

Length electrical supply cord

300.0

Door hinge

Other

Net weight

182.5

Gross weight

202.4

Multi-Flow Air Tower

Yes

Number of compressors

1

Number of independent cooling systems

1

Economy setting

No

Fast freezing function

No

Number of Door Bins - Freezer

3

Door bin adjustability - Freezer

No

Tilt-out door bins in freezer

No

Number of shelves - Freezer

Door bin adjustability - Freezer

No

Shelf Material - Freezer

Reversible Door Hinge

No

Connection Rating

Fuse protection

10

Frequency

50-60

Energy consumption

Total annual energy consumption

Universal Product Code

Door panel options

Installation typology

Full-integrated

Noise level

39

ENERGY STAR® certified

No

Length of electrical supply cord (in)

Door opening angle of 115°, fixable at 90°.

Shut-off valve for water connection must be planned next to the appliance and always be accessible.

If the water pressure exceeds 0.8 MPa (8 bar), connect pressure relief valve between water tap and hose set.

Connection


Connecting cable 3.0 m, pluggable.

Water inlet.

GAGGENAU



Measurements in mm



Measurements in mm