

Color Variants BO420102 Full glass door in Gaggenau Anthracite Width 60 cm BO420112 Stainless steel-backed full glass door Width 60 cm

Included accessories

1 x enamel baking tray. suit. pyrolitic clean. 1 x gill shelf. 1 x enamel baking tray. suit. pyrolitic clean. 1 x gill shelf. 1 x enamel baking tray. suit. pyrolitic clean. 1 x gill shelf. 1 x enamel baking tray. suit. pyrolitic clean. 1 x gill shelf.

Optional accessories BA016105 Pull-out system BA026115 Baking tray, enamelled BA036105 Wire rack, chromium-plated. BA046117 Glass trav BA056115 Heating element for baking stone and Gastronorm roaster. BA056133 Baking stone BA226105 Grill tray, enamelled BS020002 Pizza paddle, set of 2. GN340230 Gastronorm roaster in cast aluminium.

Product Variants BO421102 Oven 400 series Full glass door in Gaggenau Anthracite Width 60 cm Left-hinged Controls at the top BO420102 Oven 400 series Full glass door in Gaggenau Anthracite Width 60 cm Right-hinged Controls at the top



Handleless door / automatic door opening Pyrolytic system 9 heating methods, with baking stone function TFT touch display Panel-free appliance with surface control module Electronic temperature control from 50 °C to 300 °C Net volume 76 litres

Heating methods

Hot air. Eco hot air. Top + bottom heat. Top heat. Bottom heat. Hot air + bottom heat. Full surface grill + circulated air. Full surface grill. Baking stone function.

Handling

Automatic door opening. Rotary knob and TFT touch display operation. Clear text display. Option to save individual recipes. Information key with use indicators. Side-opening door opens up to 180° angle.

Features

Baking stone socket. Actual temperature display. Rapid heating. Timer functions: cooking time, cooking time end, timer, stopwatch, long-term timer (certified by Star-K). 60 W halogen light on the top. Enamelled side shelf supports with 4 tray levels, pyrolysis-safe.

Selected digital services (Home Connect)

Remote control and monitoring. Recipes. Home network integration for digital services (Home Connect) either via cable connection LAN (recommended) or wireless via WiFi. The use of the Home Connect functionality depends on the Home Connect services, which are not available in every country. For further information please check: homeconnect.com.

Safety

Thermally insulated door with quadruple glazing. Child lock. Safety shut-off. Cooled housing with temperature protection.

Cleaning

Pyrolytic system. Gaggenau enamel. Heated catalyser to clean the oven air.

Planning notes

Door hinge not reversible. The facade of the appliance extends 47 mm from the furniture cavity. If the handle (optional accessory) is retrofitted, the outer edge of the door handle extends 94 mm from the furniture cavity. Consider the overhang, incl. the

door handle where applicable, when planning to open drawers next to the appliance. When planning a corner solution, pay

when planning a corner solution, pay attention to the side-opening door and the minimum required distance to the wall. Characteristics Gross weight 58.5 Color / Material Front Anthracit Built-in / Free-standing Built-in Integrated Cleaning system Pyrolytic Min. required niche size for installation (HxWxD) 590-590 x 560-560 x 550 Dimensions 595 x 590 x 547 Dimensions of the packed product (HxWxD) 760 x 710 x 650 Control Panel Material without panel Door Material Glass Net weight 54.3 Usable volume of cavity 76 Cooking method Baking stone function. Bottom heat. Full width grill, Hot Air, Hot Air-Eco, Hot air grilling, Top/bottom heat, Top heat First cavity material Number of interior lights

Interior Lights - cavity 1 Pull-out system Accesso **Clock function** Alarm, Off, On, timer Included accessories 1 x enamel baking tray, suit. pyrolitic clean, 1 x glass pan, 1 x grill shelf Bake Element Wattages cavity 1 **Broil Element Wattages cavity 1** 3000 Convection Element Wattages cavity 1 2100 Microwave wattage cavity 1 Drawer wattage Energy efficiency rating

Length electrical supply cord

A Energy consumption per cycle conventional - NEW (2010/30/EC) 1.25

Energy consumption gas oven per cycle conventional - NEW (2010/30/EC) Energy consumption per cycle forced air convection - NEW (2010/30/EC) 0.83

Energy consumption gas oven per cycle forced air convection - NEW (2010/30/ EC)

Energy efficiency index (2010/30/EC) 95.4

Connection rating 3700

Fuse protection

Voltage 220-240 Frequency

50 Plug type no plug

Connecting cable type Universal Product Code

Color / Material Front Anthracite

Alternative colors available BO420112

Energy input Electric

Length of electrical supply cord (in) Required cutout/niche size for installation (in)

Dimensions of the packed product 29.92 x 25.59 x 27.95 Net weight 120.000

Gross weight 129.000



To achieve the 550 mm installation depth, the connection cable needs to follow the slanted edge on the lower right hand corner of the housing. The mains socket needs to be planned outside the built-in niche. The LAN port can be found at the back on the upper right side.

Connection

Energy efficiency class A at a range of energy efficiency classes from A+++ to D.

Total connected load 3.7 KW. Plan a connection cable.


Power consumption standby/display on 0.7 W.

Power consumption standby/display off 0.5 W.

Power consumption standby/network 1.4 W.

Time auto-standby/display on 20 min. Time auto-standby/display off 20 min. Time auto-standby/network 20 min. Plan a LAN cable.

BO420102	
Oven 400 series	
Full glass door in Gaggenau Anthraci	te
Width 60 cm	
Right-hinged	
Controls at the top	
2023-06-19	
Page 2	



GAGGENAU