



BS450101
Combi-steam oven 400 series
Full glass door in Gaggenau Anthracite
Width 60 cm
Right-hinged
Controls at the top



Handleless door / automatic door opening / door opening via voice assistant possible
 Water tank for fresh and waste water
 Cleaning system, fully automatic
 Large cavity
 2 LED light sources
 External steam generation
 Steaming without pressure
 Hot air 30 °C to 230 °C can be combined with chosen humidity level of 0%, 30%, 60%, 80% or 100%
 Sous-vide cooking with accurate temperature regulation
 Full surface grill behind glass ceramic, combinable with circulated air up to 230 °C and steam
 Automatic programmes
 Core temperature probe with estimation of cooking time
 Hot air fan rotates in both directions for ideal heat distribution
 TFT touch display
 Panel-free appliance with surface control module
 Electronic temperature control from 30 °C bis 230 °C
 Net volume 50 litres

Heating methods

Hot air + 100 % humidity.
 Hot air + 80 % humidity.
 Hot air + 60 % humidity.
 Hot air + 30 % humidity.
 Hot air + 0 % humidity.
 Low temperature cooking.
 Sous-vide cooking.
 Full surface grill level 1 + humidity.
 Full surface grill level 2 + humidity.
 Full surface grill + circulated air.
 Dough proofing.
 Defrosting.
 Regenerating.

Handling

Automatic door opening.
 Rotary knob and TFT touch display operation.
 Clear text display.
 Option to save individual recipes (incl. core temperature probe).
 Personalisation of automatic programmes.
 Information key with use indicators.
 Side-opening door opens up to 180° angle.

Features

Full surface grill 2 KW behind glass ceramic.
 2 removable 1.7 litre water tanks.
 Misting.
 Water level warning.
 Three-point core temperature probe with automatic shut-off and estimation of cooking time.
 Automatic programmes.
 Actual temperature display.
 Timer functions: cooking time, cooking time end, timer, stopwatch, long-term timer (certified by Star-K).
 Automatic boiling point detection.
 2 x LED light on the side.
 Hygienic stainless steel cooking interior.
 3 tray levels.

Color Variants

BS450101
Full glass door in Gaggenau Anthracite
Width 60 cm
BS450111
Stainless steel-backed full glass door
Width 60 cm

Included accessories

1 x grid.
 1 x pluggable meat probe.
 1 x STS tray.
 punched.
 40 mm deep.
 1 x STS tray.
 unpunched.

Optional accessories

BA010301
Triple telescopic pull-out rack
BA020360
Cooking container, stainless steel, unperforated, 40 mm deep, 5 l.
BA020370
Cooking container, stainless steel, perforated, 40 mm deep, 5 l.
BA020380
Cooking container, non-stick, unperforated, 40 mm deep, 5 l.
BA020390
Insert, non-stick, perforated, 40 mm deep, 5 l.
BA046117
Glass tray
CLS10040
Cleaning cartridges, set of 4
GN010330
Adapter for gastronorm insert and roaster.
GN114130
Gastronorm insert, stainless steel, GN 1/3
GN114230
Gastronorm insert, stainless steel, GN 2/3
GN124130
Gastronorm insert, stainless steel, GN 1/3
GN124230
Gastronorm insert, stainless steel, GN 2/3
GN340230
Gastronorm roaster in cast aluminium.

Product Variants

BS451101
Combi-steam oven 400 series
Full glass door in Gaggenau Anthracite
Width 60 cm
Left-hinged
Controls at the top
BS454101

Characteristics

Color / Material Front
 Anthracite
Built-in / Free-standing
 Built-in
Door opening
 Lateral
Required niche size for installation (HxWxD)
 450-450 x 560-560 x 550
Dimensions
Dimensions of the packed product (HxWxD)
 585 x 660 x 695
Control Panel Material
 Glass
Door Material
 Glass
Net weight
 46.351
Approval certificates
 CCC, CE, China, China ROHS 20, Eurasian, G-Mark, Ukraine, VDE
Length electrical supply cord
 175
Cooking method
 , Defrost, fermentation, grill + steam, Hot Air, Hot air + steam 100%, Hot air + steam 30%, Hot air + steam 60%, Hot air + steam 80%, Hot air grilling, Regeneration
Time-setting Options
Electrical connection rating
Fuse protection
 16
Voltage
 220-240
Frequency
 50
Plug type
 Gardy plug w/ earthing
Connecting cable type
Approval certificates
 CCC, CE, China, China ROHS 20, Eurasian, G-Mark, Ukraine, VDE
Universal Product Code
Color / Material Front
 Anthracite
Alternative colors available
 BS450111
Energy input
 Electric
Fuse protection
 16
Voltage
 220-240
Frequency
 50
Approval certificates
 CCC, CE, China, China ROHS 20, Eurasian, G-Mark, Ukraine, VDE
Length of electrical supply cord (in)
Plug type
 Gardy plug w/ earthing
Appliance Dimensions (h x w x d) (in)
Required cutout/niche size for installation (in)
Dimensions of the packed product
Net weight
 102.000
Gross weight
 107.000

Consumption and connection features

2021-12-14
 Page 1

Home network integration for digital services (Home Connect) either via cable connection LAN (recommended) or wireless via WiFi.
 The use of the Home Connect functionality depends on the Home Connect services, which are not available in every country. For further information please check: home-connect.com.

Safety

Child lock.
 Safety shut-off.
 Cooled housing with temperature protection.

Cleaning

Cleaning programme, fully automatic.
 Descaling programme for the steam generator.
 Drying programme.
 Automatic drying of the cavity at the end of the cooking process.
 Strainer filter, removable.
 Water tank, dishwasher-safe.
 Demo cleaning programme.


Planning notes

Door hinge not reversible.
 No other electrical appliances should be installed above the BS.
 The facade of the appliance extends 47 mm from the furniture cavity.
 Consider the overhang when planning to open drawers next to the appliance.
 When planning a corner solution, pay attention to the 90° door opening angle.
 The mains socket needs to be planned outside the built-in niche.
 The LAN port can be found at the back on the lower left side.
 Special accessories (order as spare part):
 Part No. 17002490 Descaling tablets.

Connection


Energy efficiency class A at a range of energy efficiency classes from A+++ to D.
 Total connected load 3.1 KW.
 Connecting cable 1.8 m with plug.
 Plan a LAN cable.
 Power consumption standby/display on 0.8 W.
 Power consumption standby/display off 0.5 W.
 Power consumption standby/network 1.8 W.
 Time auto-standby/display on 20 min.
 Time auto-standby/display off 20 min.
 Time auto-standby/network 20 min.
 Please check the user manual for how to switch off the WiFi module.

BS450101
Combi-steam oven 400 series
Full glass door in Gaggenau Anthracite
Width 60 cm
Right-hinged
Controls at the top
2021-12-14
Page 2



Δ Socket
measurements in mm

Side view of BS 454/455 above BO



measurements in mm