

Color Variants EB333111 stainless steel Width 90 cm

Included accessories

1 x enamel baking tray. suit. pyrolitic clean. 1 x rotary spit. 1 x grill shelf. 1 x grill tub with grid. 1 x pluggable meat probe.

Optional accessories BA018105 Pull-out system BA028115 Baking tray, enamelled BA038105 Wire rack, chromium-plated. BA058115 Heating element for baking stone and Gastronorm roaster. BA058133 Baking stone BA090100 Black rotary knobs for EB 333, set of 2 BS020002 Pizza paddle, set of 2. GN340230 Gastronorm roaster in cast aluminium.

EB333111 Oven stainless steel Width 90 cm

Α

One-piece front-hinged door with 3 mm precision crafted stainless steel front door panel Cushioned door opening and closing system Diagonally positioned light sources for optimal interior lighting Pvrolvtic system 17 heating methods with core temperature probe, rotisserie spit and baking stone function Automatic programmes Core temperature probe with estimation of cooking time Hot air fan rotates in both directions for ideal heat distribution TFT touch display Panel-free appliance with control module behind glass Electronic temperature control from 30 °C to 300 °C Net volume 83 litres

Heating methods

Hot air. Eco hot air. Top + bottom heat. Top + 1/3 bottom heat. Top heat. 1/3 top + bottom heat. Bottom heat. Hot air + bottom heat. Hot air + 1/3 bottom heat. Full surface grill + circulated air. Full surface grill. Compact grill. Baking stone function. Roaster function. Dough proofing. Defrosting Keeping warm

Handling

Rotary knob and TFT touch display operation. Clear text display. Option to save individual recipes (incl. core temperature probe). Personalisation of automatic programmes. Information key with use indicators. Front-hinged door with 90° door opening angle.

Features

Three-point core temperature probe with automatic shut-off and estimation of cooking time. Automatic programmes. Rotisserie spit. Baking stone socket. Actual temperature display Rapid heating. Timer functions: cooking time, cooking time end, timer, stopwatch, long-term timer (certified by Star-K). 60 W halogen light on the top 2 x 10 W halogen light on the side. Enamelled side shelf supports with 3 tray levels, pyrolysis-safe. Home network integration for digital services (Home Connect) either via cable connection LAN (recommended) or wireless via WiFi. The use of the Home Connect functionality depends on the Home Connect services, which are not available in every country. For further information please check: homeconnect.com.

Characteristics

Color / Material Front Stainless steel Built-in / Free-standing Built-in Integrated Cleaning system Pvrolvtic Required niche size for installation (HxWxD) 475-475 x 860-860 x 560 Dimensions 480 x 890 x 550 Dimensions of the packed product (HxWxD) 660 x 730 x 1000 Control Panel Material Stainless steel Door Material Stainless steel behind glass Net weight 79.011 Usable volume of cavity 83 Cooking method Baking stone function, Bottom heat,

Conventional heat, Defrost, Dough proving setting, Full width grill, Half width grill, Hot Air, Hot Air-Eco, Hot air grilling, Roaster function, Top heat, warming

First cavity material Number of interior lights

Approval certificates

Australia Standards, CCC, CE, China, China ROHS 20, Eurasian, G-Mark, Ukraine, VDE

Length electrical supply cord Interior Lights - cavity 1

Pull-out system Accessory

Clock function Alarm, Off, On, timer

Included accessories

1 x enamel baking tray,suit. pyrolitic clean, 1 x rotary spit, 1 x grill shelf, 1 x grill tub with grid, 1 x pluggable meat probe

Bake Element Wattages cavity 1 Broil Element Wattages cavity 1 3900

Convection Element Wattages cavity 1 1900

Microwave wattage cavity 1 Drawer wattage Energy efficiency rating

Energy consumption per cycle conventional - NEW (2010/30/EC)

Energy consumption gas oven per cycle conventional - NEW (2010/30/EC) Energy consumption per cycle forced air convection - NEW (2010/30/EC) 0.86

Energy consumption gas oven per cycle forced air convection - NEW (2010/30/ EC)

Energy efficiency index (2010/30/EC) 95.6

Connection rating 5380

Fuse protection

Voltage

220-240
Frequency
50
Plug type
fixed connection, no plug

Connecting cable type Universal Product Code Color / Material Front

Stainless steel Alternative colors available

Energy input Electric Approval certificates Australia Standards, CCC, CE, China,

China ROHS 20, Eurasian, G-Mark, Ukraine, VDE Length of electrical supply cord (in)



Thermally insulated door with quintuple glazing. Child lock. Safety shut-off. Cooled housing with temperature protection.

Cleaning

Pyrolytic system. Gaggenau enamel. Heated catalyser to clean the oven air.

Planning notes

The door panel surface of the appliance extends 40 mm from the furniture cavity. The outer edge of the door handle

The outer edge of the door handle extends 90 mm from the furniture cavity.

For installation underneath cooktops: Distance between the underside of the cooktop and the top edge of the oven cavity: min. 15 mm. The planning notes for the cooktops (particularly regarding ventilation, gas/electric connection) must be taken into account.

To achieve the 550 mm installation depth, the connection cable needs to follow the slanted edge on the corner of the housing.

The mains socket needs to be planned outside the built-in niche.

The LAN port can be found at the back on the upper left side.

Connection

Energy efficiency class A at a range of energy efficiency classes from A+++ to D.

Total connected load 5.4 KW. Plan a connection cable.

Plan a LAN cable.

Power consumption standby/display on 0.7 W.

Power consumption standby/display off 0.5 W.

Power consumption standby/network 1.5 W.

Time auto-standby/display on 20 min. Time auto-standby/display off 20 min. Time auto-standby/network 20 min. Please check the user manual for how to switch off the WiFi module.

GAGGENAU

EB333111 Oven stainless steel Width 90 cm 2022-01-29 Page 2



