PRODUCT SPEC SHEET

Showroom collection: Evolution 250 food waste

SHOWROOM COLLECTION



Special edition Evolution 250 food waste disposer

This special edition version of our quietest and most powerful food waste disposer stands out from the crowd. It features black trim, a new style trim shell and a premium stainless steel sink stopper with cover. It is supplied with built-in air switches in black, chrome and brushed steel and is supported by an 8 year parts and service guarantee.

Features

- Built-in air switch in black, chrome and brushed steel
- 8 year guarantee
- Deluxe stopper cover
- New style trim shell
- Evolution Ultra-quiet technology
- Evolution 3-stage grind technology

- Auto-reverse grinding action
- High-torque Dura-Drive[™] induction motor
- Stainless steel grind elements and grind chamber
- Overload protection
- Quick Lock[®] mounting assembly for faster, easier installation






PRODUCT SPEC SHEET

Showroom collection: Evolution 250 food waste

Dimensions (mm)



Compatible with Cover control



For those who prefer the on/off switch built right into the disposer cover, InSinkErator offers the cover control accessory. It's just right for efficient batch feed operation.

(Not available in all markets.)

Specifications (mm)

Type of feed	Continuous		
On/Off Control	Wall switch or built-in air switch		
Motor	Single phase		
Reversing	Auto-reverse grind system		
Time Rating	Intermittent		
Lubrication	Permanently lubricated upper & lower bearings		
Shipping Weight (Approx.)	11.6kg		
Unit Finish	Stainless steel light Gray TEN-1706		
Overall Height	344mm		
Grind Technology	3-stage grind technology Power booster circuit with microprocessor technology included		
Sound Technology	Anti-vibration mounting and tailpipe Quiet sink baffle multi layer sound insulation Stainless steel strainer basket & plug		
Grind Chamber Capacity	1180ml		
Motor Protection	Manual reset overload		
Average Water Usage	Approximately 4.0L per person per day		
Average Electrical Usage	3-4KWH per annum		
Drain Connection	1-1/2" (3.81cm) anti vibration (hose clamp)		
Dishwasher Drain Connection	Yes		

Volts/Hz	HP	RPM	Average Load
120V, 60Hz	1.0	1725	10.2 A
220-240V, 50Hz	.75	1425	380 W
220-240V, 60Hz	.75	1725	370 W



InSinkErator Suite 10, Building 6 Hatters Lane Croxley Green Business Park Watford, Herts WD18 8YH United Kingdom Sales tel: (0) 1 923 297 880 Service tel: (0) 800 389 3715 www.insinkerator.co.uk

InSinkErator Emerson Electric Co. 4700 21st Street Racine, WI 53406-5093 USA Sales/Service tel: 262-554-5432 www.insinkerator.com/worldmap.

