

Color Variants RB289300 With fresh cooling close to 0 °C Fully integrated

Included accessories

2 x cold accumulator. 2 x egg tray. 1 x ice cube tray. 2 x wooden bottle holder magnetic.

Optional accessories RA238030

RA23030 Solid maple bottle support with magnetic connector, oiled RA430100 Storage container with transparent lid, anthracite. RB289300 Vario fridge-freezer combination 200 series With fresh cooling close to 0 °C Fully integrated

Niche width 56 cm, Niche height 177.5 cm



Interior with precision-fitted, solid aluminium elements in Gaggenau Light Bronze

Extendable shelves and drawers Warm white and glare-free LED light 4 climate zones incl. 2 fresh cooling drawers close to 0 °C Height-adjustable, extendable safety glass shelves, set in solid aluminium

profiles Cushioned door closing system allowing a soft and controlled door closure

Smooth running fully extendable telescopic pull-out racks and a cushioned closing system allow a soft and controlled closure of the drawers Solid maple bottle supports with magnetic connector Total volume 223 litres

Handling Electronic temperature control with digital display. Touch keys.

Technical Features

Automatic defrosting with defrost water evaporation. Cushioned door closing system from 20° door opening angle, integrated in door hinge. Open-door and malfunction alarm. Holiday mode. Home network integration for digital services (Home Connect) wireless via WiFi. The use of the Home Connect functionality depends on the Home Connect services, which are not available in every country. For further information please check: homeconnect.com. Cooling Fast cooling. Temperature adjustable from +3 °C to +8 °C 2 height-adjustable safety glass shelves, partly extendable. 1 frosted white glass shelf.

2 oiled, solid maple bottle supports with magnetic connector, can be increased to 5 supports per shelf. A total of 9 bottles (based on a 0.75 l bottle) can be stored on one level using 5 bottle supports. The bottle supports are also suitable

for storing champagne bottles and magnums.

1 large aluminium door rack for bottles. 1 aluminium door rack. Warm white interior lighting (3500 K) with integrated glare-free LED side lights. Volume 101 litres.

Fresh cooling close to 0 °C

Drawers with solid aluminium handles and signature drawer front with a gradual frosted surface. 1 fully extendable fresh cooling drawer close to 0 °C, illuminated. Humidity can be adjusted manually. Ideal for fruit and vegetables. 1 fully extendable fresh cooling drawer close to 0 °C, illuminated. Ideal for meat, fish and poultry. Volume 55 litres.

Freezing

No-frost technology with fast freezing.

Characteristics

Energy Efficiency Class (Regulation (EU) 2017/1369)

Average annual energy consumption in kilowatt hour per year (kWh/a) (EU) 2017/1369 201

Sum of volume of frozen compartments (EU 2017/1369) 67

Sum of volume of chill compartments (EU 2017/1369)

156 Airborne acoustical noise emissions

(EU 2017/1369) 37 Airborne acoustical noise emission

class (EU 2017/1369) C Built-in / Free-standing

Built-in Number of compressors

1

Number of independent cooling systems

Width of the appliance 558 Height

Depth of the product

Net weight

75.6

Required niche size for installation (HxWxD) 1775.0 x 560 x 550 Door panel options

Not possible Door hinge Right reversible

Number of Adjustable Shelves in fridge compartment

Shelves for Bottles Yes Frost free system Freezer Interior ventilator No Reversible Door Hinge Yes Length electrical supply cord 230 Noise level 37

Multi-Flow Air Tower No Fast cooling switch

Yes Fast freezing switch Yes

Temperature Controlled Drawer

Humidity Control Drawer

Number of Door Bins - Refrigerator

Door bin adjustability - Refrigerator

Tilt-out door bins in fridge

Gallon Storage

Number of Gallon storage

Motorized Shelf

No
Material of the shelves
Safety glass
Type of Light
Door opened indicator freezer
No
Drawers with telscopic rails
none
Automatic motor-driven ice-maker
No
Ice Storage Capacity
Ice Cubes per Day
Connection rating
90
Free to the teleform of the shelves

Fuse protection 10



Temperature adjustable from -14 °C to -24 °C. 4-star freezer compartment. Drawers with solid aluminium handles and signature drawer front with a gradual frosted surface. Defrost assistance. Freezing capacity 7 kg /24 h. Storage time after a malfunction 8 h. 3 freezer drawers, 1 of which extra large. 2 safety glass shelves. Volume 67 litres.

Consumption data

Energy efficiency class D at a range of energy efficiency classes from A to G. Energy consumption 201 kWh/year. Noise level 37 dB (A) re 1 pW.

Planning notes

Flat hinge. Door hinge right, reversible. Door opening angle of 115°, fixable at 90°. Max. door panel weight: Upper door 19 kg. Lower door 19 kg.

Connection

Total connected load 0.090 KW. Connecting cable 2.3 m with plug.









